


ANTIDARK

EASY W2100 datasheet



W2100

2X10W LED. Dimmable. 230V. 2700K. 2X643lm. 64 lm/W. BA32°. CRI90+. 35.000h. IP20. 360° Vertical | 90° Horizontal
Ø:10cm X2. H: 10.5cm. L: 21.0cm. Aluminium base | PVC screen. 5 year warranty.

2x10W LED. Dæmpbar. 230V. 2700K. 2x643lm. 64 lm/W. BA32°. CRI90+. 35.000h. IP20. 360° Vertikal | 90° Horizontal
Ø:10cm X2. H: 10.5cm. L: 21.0cm. Aluminiums base | PVC skærm. 5 års garanti.

2-215-09-1
White/Hvid
EAN 5706872018680

2-215-09-2
Black/Sort
EAN 5706872019069

W2100 wirehole

2X10W LED. Dimmable. 230V. 2700K. 2X643lm. 64 lm/W. BA32°. CRI90+. 35.000h. IP20. 360° Vertical | 90° Horizontal
Ø:10cm X2. H: 10.5cm. L: 21.0cm. Aluminium base | PVC screen. With wire hole cutout. 5 year warranty.

2x10W LED. Dæmpbar. 230V. 2700K. 2x643lm. 64 lm/W. BA32°. CRI90+. 35.000h. IP20. 360° Vertikal | 90° Horizontal
Ø:10cm X2. H: 10.5cm. L: 21.0cm. Aluminiums base | PVC skærm. Med ledningshul. 5 års garanti.

2-215-09-10
White/Hvid
EAN 5706872019847

2-215-09-20
Black/Sort
EAN 5706872019854