

ANTIDARK

EASY W3100 datasheet



EASY W3100

28.2W LED. Dimmable. 230V. 2700K. 2220lm. BA32°. CRI90+. 50.000h. IP20.
360° Vertical | 90° Horizontal
Ø:10cm X3. H: 10.5cm. L: 32.4cm. Aluminium base. 5 year warranty.

28,2W LED. Dæmpbar. 230V. 2700K. 2220lm. BA32°. CRI90+. 50.000h. IP20. 360° Vertikal | 90° Horisontal
Ø:10cm X3. H: 10.5cm. L: 32.4cm. Aluminiums base. 5 års garanti.

2-215-11-1

White/ hvid

EAN 5706872019069

2-215-11-2

Black/ sort

EAN 5706872019625

EASY W3100 Wirehole

28.2W LED. Dimmable. 230V. 2700K. 2220lm. BA32°. CRI90+. 50.000h. IP20.
360° Vertical | 90° Horizontal
Ø:10cm X3. H: 10.5cm. L: 32.4cm. Aluminium base. With wire hole cutout.
5 year warranty.

28,2W LED. Dæmpbar. 230V. 2700K. 2220lm. BA32°. CRI90+. 50.000h. IP20.
360° Vertikal | 90° Horisontal
Ø:10cm X3. H: 10.5cm. L: 32.4cm. Aluminiums base. Med ledningshul.
5 års garanti.

2-215-11-10

White/ hvid

EAN 5706872019885

2-215-08-20

Black/ sort

EAN 5706872019533