

# ANTIDARK

## EASY W4100 datasheet



### EASY W4100

**37W LED. Dimmable. 230V. 2700K. 2922lm. BA32°. CRI90+. 50.000h. IP20.  
360° Vertical | 90° Horizontal  
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminium base. 5 year warranty.**

**37W LED. Dæmpbar. 230V. 2700K. 2922lm. 64 lm/W. BA32°. CRI90+. 50.000h. IP20.  
360° Vertikal | 90° Horisontal  
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminiums base. 5 års garanti.**

**2-215-12-1**

**White/ hvid**

**EAN 5706872019069**

### EASY W4100 Wirehole

**37W LED. Dimmable. 230V. 2700K. 2922lm. BA32°. CRI90+. 50.000h. IP20.  
360° Vertical | 90° Horizontal  
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminium base. With wire hole cutout.  
5 year warranty.**

**37W LED. Dæmpbar. 230V. 2700K. 2922lm. 64 lm/W. BA32°. CRI90+. 50.000h. IP20.  
360° Vertikal | 90° Horisontal  
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminiums base. Med ledningshul.  
5 års garanti.**

**2-215-12-10**

**White/ hvid**

**EAN 5706872019892**