

ANTIDARK

EASY W4100 datasheet



EASY W4100

37W LED. Dimmable. 230V. 2700K. 2922lm. BA32°. CRI90+. 50.000h. IP20.
360° Vertical | 90° Horizontal
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminium base | PVC screen. 5 year warranty.

37W LED. Dæmpbar. 230V. 2700K. 2922lm. 64 lm/W. BA32°. CRI90+. 50.000h. IP20.
360° Vertikal | 90° Horisontal
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminiums base | PVC skærm. 5 års garanti.

2-215-12-1

White/ hvid

EAN 5706872019069

EASY W4100 Wirehole

37W LED. Dimmable. 230V. 2700K. 2922lm. BA32°. CRI90+. 50.000h. IP20.
360° Vertical | 90° Horizontal
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminium base | PVC screen. With wire hole cutout.
5 year warranty.

37W LED. Dæmpbar. 230V. 2700K. 2922lm. 64 lm/W. BA32°. CRI90+. 50.000h. IP20.
360° Vertikal | 90° Horisontal
Ø:10cm X4. H: 10.5cm. L: 21.2cm. Aluminiums base | PVC skærm. Med ledningshul.
5 års garanti.

2-215-12-10

White/ hvid

EAN 5706872019892