



SLC ONE SOFT R68-83 WH 600TED

927 IP44 36°

One downlight for all applications! Deep recessed LED for low glare. For new and rehab projects. Can be mounted into insulation, up to the moisture barrier.



Light technic	
Product ID	SLC1124
Beam angle	36 °, Medium beam 21-40° °
Colour rendering index (CRI/Ra)	90
Type of light source	LED
Lamp efficacy	75 lm/W
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Rated luminous flux according to IEC 62722-2-1	600 lm
Colour of light	White
Luminous flux	600 - 600 lm
Rated life time L80/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Type of control signal	Trailing Edge
CE	Yes
Exterior color	White
Dimmable	Yes
Dimming range	1-100% %
Driver output current	180 mA
EMC	Yes
ENEC	Yes
IP class	IP44
Operating temperature	-10°C ~ +45°C °C

14.01.2021

Subject to changes and printing errors

RoHs	Yes
SELV	Yes
Protection class	II
Colour housing	White
Surface protection	Powder coating
Suitable for lamp power	8 - 8
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP44
Control gear included	Yes
Surface brushed	No
Max. system power	8 W
Adjustability	Not adjustable
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming DALI	Yes
Dimming phase cut-off	Yes
Power factor	0.9
Dimming method	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC/DC
Strain relief	Yes
Nominal voltage	220 - 240 V
Output	
LED nominal current at constant current	180 - 180 mA
Installation	
Cut-out hole (Ø)	68-83 mm
Height/depth	46 mm
Built-in width	67 mm
Height	45.4 mm
Built-in height/depth	46 mm
Length	90 mm
Width	90 mm
Installation depth	46 mm
Can be installed directly into the insulation	Yes
Type of installation	Recessed
Outer diameter	90 mm

14.01.2021
Subject to changes and printing errors

Conductor cross section	0.35 mm ²
Connection type	Plug clamp
Built-in diameter	68 mm
Suitable for suspended mounting	No
Number of poles	3
Suitable for wall mounting	No
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Product gross weight	350 g
Imported by	The Light Group
D-pack gross weight	20 kg
Product gross length	111 mm
Pcs carton	50
D-pack height	23.2 cm
D-pack width	53.5 cm
D-pack length	52 cm
Brand	SLC
Product gross width	101 mm
Product gross height	102 mm
General data	
GTIN	7070938061421
Pallet length	1200 mm
M-pack length	535 mm
F-pack length	100 mm